Data Sheet

Coaxial Cable Connector 16_BNC-75-2-3/133_N

Description

Right angle cable plug

Interface standards Interface compatible with IEC 61169-8



Technical Data

Electrical Data Impedance Interface frequency max.	75 Ω 1 GHz
Mechanical Data Centre contact Outer contact Weight	soldered crimped 0.0164 kg
Environmental Data Operating temperature 2011/65/EU (RoHS)	-65 °C to 165 °C compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
Crimp ferrule	Copper	

Related Documents

Outline drawing Catalogue drawing Assembly instruction	DOU-00071611 DOU-00006046 DOC-0000179255
Ordering Information	
Single package	16_BNC-75-2-3/133_NE
Additional Information	
Suitable cables	RG_179_B/U, RG_187_A/U

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

