## **Data Sheet**

# Coaxial Panel Connector 22\_TNC-50-0-2/133\_N

### Description

Straight bulkhead receptacle jack

Interface standards IEC 60169-17\_MIL-STD-348A/313\_CECC 22200



**HUBER+SUHNER** 

#### **Technical Data**

Electrical Data	
Impedance	50 Ω
Interface frequency max.	11 GHz
Mechanical Data	
Number of matings	500
Weight	0.0079 kg
Environmental Data	
Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including	compliant
2015/863 and 2017/2102)	

#### **Material Data**

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating

#### **Related Documents**

Outline drawing	DOU-00011566
Catalogue drawing	DCA-00011568
Mounting hole	DOU-00008762

#### **Ordering Information**

Single package

22\_TNC-50-0-2/133\_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.