Data Sheet

Coaxial PCB Connector 85_SMB-Z50-0-19/111_N

Description

Right angle PCB jack

Interface Standards IEC 60169-10_MIL-STD-348A/311_CECC 22130

Technical Data

Electrical Data Impedance Interface frequency max.	50 Ω 4 GHz	
Mechanical Data Board mounting type Weight	through holes 0.0021 kg	
Environmental Data Operating temperature 2011/65/EU (RoHS) Material Data	-40 °C to 100 °C compliant	
Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Zinc Alloy	SUCOPRO Plating
Body	Zinc Alloy	SUCOPRO Plating
Insulator	PFA / PTFE	
Related Documents		
Outline drawing Catalogue drawing	DOU-00013184 DCA-00013186	
Ordering Information		
Bulk 100 pcs package Single package	85_SMB-Z50-0-19/111_NH 85_SMB-Z50-0-19/111_NE	
Remarks		

PCB connector with stand-offs

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

