Data Sheet

Coaxial Panel Connector 22_SHV-50-0-6/133_N



Description

Straight bulkhead receptacle jack

Interface standards IEC 60498_MIL-STD-348A/314



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & 50 \ \Omega \\ \text{Interface frequency max.} & 0.3 \ \text{GHz} \end{array}$

Mechanical Data

Chassis torque2 NmNumber of matings500Weight0.0111 kg

Environmental Data

Operating temperature -55 °C to 100 °C 2011/65/EU (RoHS) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PS (Polystyrene)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating

Related Documents

Outline drawing DOU-00011058
Catalogue drawing DCA-00010449
Mounting hole DOU-00008762

Ordering Information

Single package 22_SHV-50-0-6/133_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.