

RF TERMINATION Type 65_BNC-75-0-1

Description

Standard Termination, Low Power



Product Configuration

Connector	BNC plug (male)
Interface standards	IEC 60169-8_MIL-STD-348A/301_CECC 22120

Technical Data

Electrical Data

Nominal Impedance	75 Ω
Frequency range	0 to 1 GHz
VSWR max.	1.1
Power rating	1 Watt average power up to 30 °C ambient temperature, linearly derated to 0 Watt at 130 °C ambient temperature. 800 Watt peak power

Mechanical Data

Weight	0.014 kg
--------	----------

Environmental Data

Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102)	-40 °C to 130 °C compliant
--	-------------------------------

Material Data

Piece Part	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00020116
-----------------	--------------

Ordering Information

Single Packaging Packaging	65_BNC-75-0-1/133_NE
-------------------------------	----------------------