

## Coaxial Cable Connector 24\_BNC-50-3-8/133\_N

### Description

Straight bulkhead cable feed through

Interface standards

IEC 60169-8\_MIL-STD-348A/301\_CECC 22120



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 4 GHz

#### Mechanical Data

Centre contact crimped  
Outer 2contact crimped  
Weight 0.0161 kg

#### Environmental Data

Operating temperature -65 °C to 165 °C  
2011/65/EU (RoHS) compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Brass	
Washer	Bronze	
Crimp ferrule	Copper	

### Related Documents

Outline drawing DOU-00008940  
Catalogue drawing DCA-00008942  
Assembly instruction DOC-0000179061  
Mounting hole DOU-00008751

### Ordering Information

Single package 24\_BNC-50-3-8/133\_NE

### Additional Information

Suitable cables RG\_223\_U, ENVIROFLEX\_142, G\_03232\_D-01