

Within Series Adaptor 34_SHV-50-0-3/100_N

Description

Bulkhead adaptor jack/jack
SHV jack (female) / SHV jack (female)

Hermetic sealed connector

Interface standard
Series SHV - IEC 60498_MIL-STD-348A/314



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 0.3 GHz

Mechanical Data

Number of matings 500
Weight 0.0419 kg

Environmental Data

Operating temperature -65 °C to 165 °C
2011/65/EU (RoHS) not compliant

Material Data

Interface - SHV jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	Silver Plating
Body	Brass	Silver Plating
Insulator	PFA / PTFE	
Gasket	FKM (Fluoro elastomer, FPM)	

Interface - SHV jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	Silver Plating
Body	Brass	Silver Plating
Insulator	PFA / PTFE	
Gasket	FKM (Fluoro elastomer, FPM)	

Related Documents

Outline drawing DOU-00013636
Mounting hole DOU-00008751

Ordering Information

Single package 34_SHV-50-0-3/100_NE

Remarks

Hermetically sealed: Leakage rate 10⁻⁷ Torr l/sec (atm cc/s)

Within Series Adaptor 34_SHV-50-0-3/100_N