### **Data Sheet**



## Coaxial Panel Connector 22\_MMBX-50-0-2/111\_N

#### **Description**

Straight bulkhead receptacle jack

Interface standards SUHNER-MMBX

# 2

#### **Technical Data**

**Electrical Data** 

 $\begin{array}{ll} \mbox{Impedance} & \mbox{50} \ \Omega \\ \mbox{Interface frequency max.} & \mbox{12.4 GHz} \end{array}$ 

**Mechanical Data** 

Number of matings 100
Weight 0.0011 kg

**Environmental Data** 

Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102) -55 °C to 155 °C compliant

#### **Material Data**

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PTFE / LCP	

#### **Related Documents**

Outline drawing DOU-00017333
Catalogue drawing DCA-00086279
Mounting hole DCA-00086278

#### **Ordering Information**

Tray package 22\_MMBX-50-0-2/111\_NY

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.