

Coaxial Panel Connector 22_MMCX-50-0-1/111_O

Description

Straight bulkhead receptacle jack

Interface standards SUHNER-MMCX





Technical Data

Electrical Data		
Impedance	50 Ω	
Interface frequency max.	6 GHz	
Mechanical Data		
Number of matings	500	
Weight	0.0008 kg	
Environmental Data		
Operating temperature	-55 °C to 155 °C	
2011/65/EU (RoHS)	compliant	
Material Data		
Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	
Fastening nut	Brass	Gold Plating (without Nickel underplating)

Related Documents

DOU-00010459
DCA-00010461
DOU-00009144

Ordering Information

Bulk 100 pcs package	
Single package	

22_MMCX-50-0-1/111_OH 22_MMCX-50-0-1/111_OE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.