

Between Series Adaptor 34_BNC-QLA-01-1/1--_U

Description

Bulkhead adaptor jack/jack
BNC jack (female) / QLA-01 jack (female)

Interface standards
Series BNC - IEC 61169-8_MIL-STD-348A/301_CECC 22120
Series QLA-01 - NIM-CAMAC-Standard CD/N549



Technical Data

Electrical Data

Impedance other Ω
Interface frequency max. 1.4 GHz

Mechanical Data

Number of matings 500
Weight 0.0092 kg

Environmental Data

Operating temperature -55 °C to 150 °C
2011/65/EU (RoHS - including
2015/863 and 2017/2102) compliant

Material Data

Interface - BNC jack (female)

| Piece Parts | Material | Surface Plating |
|----------------|------------------------|--|
| Centre contact | Copper Beryllium Alloy | Gold Plating (without Nickel underplating) |
| Outer contact | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PFA / PTFE | |

Interface - QLA-01 jack (female)

| Piece Parts | Material | Surface Plating |
|----------------|------------------------|--|
| Centre contact | Copper Beryllium Alloy | Gold Plating (without Nickel underplating) |
| Outer contact | Bronze | Gold Plating (Nickel underplated) |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PFA / PTFE | |

Related Documents

Catalogue drawing DCA-00014159
Mounting hole DOU-00008762

Ordering Information

Single package 34_BNC-QLA-01-1/1--_UE