# **Data Sheet**



# Coaxial PCB Connector 82\_BNC-75-0-2/122\_N

# **Description**

Straight PCB jack

Interface Standards
Interface compatible with IEC 61169-8



#### **Technical Data**

**Electrical Data** 

 $\begin{array}{ll} \text{Impedance} & 75\,\Omega \\ \text{Interface frequency max.} & 1\,\text{GHz} \end{array}$ 

**Mechanical Data** 

Board mounting type through holes Weight 0.0065 kg

**Environmental Data** 

Operating temperature -65 °C to 165 °C 2011/65/EU (RoHS - including 2015/863 and 2017/2102) compliant

#### **Material Data**

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Nickel Plating
Body	Brass	Nickel Plating
Insulator	PFA / PTFE	

# **Related Documents**

Outline drawing DOU-00012999
Catalogue drawing DCA-00013001
Mounting hole DOU-00012084

# **Ordering Information**

 Bulk 100 pcs package
 82\_BNC-75-0-2/122\_NH

 Single package
 82\_BNC-75-0-2/122\_NE

#### Remarks

PCB connector with stand-offs

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.