

Coaxial Cable Connector 11_N-50-7-69/133_N

Description

Straight cable plug

SUHNER full crimp cable attachment
Ingress protection according to IP67



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	11 GHz

Mechanical Data

Centre contact	crimped
Outer contact	crimped
Weight	0.0345 kg

Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
Crimp ferrule	Copper	

Related Documents

Outline drawing	DOU-00008098
Catalogue drawing	DCA-00245537
Assembly instruction	DOC-0000311731

Ordering Information

Single package	11_N-50-7-69/133_NE
----------------	---------------------

Additional Information

Suitable cables	S_07162_B, SPUMA_400-FR, SPUMA_400-UF, LMR-400
Interface standards	IEC 61169-16_MIL-STD-348A/304_CECC 22210