### **Data Sheet**

# HUBER+SUHNER Excellence in Connectivity Solutions

## Coaxial Panel Connector 22\_QLA-01-0-2/112\_N

#### **Description**

Straight bulkhead receptacle jack

Interface standards
NIM-CAMAC-Standard CD/N549



#### **Technical Data**

**Electrical Data** 

 $\begin{array}{ll} \text{Impedance} & 50 \ \Omega \\ \text{Interface frequency max.} & 1.4 \ \text{GHz} \end{array}$ 

**Mechanical Data** 

Number of matings 10000 Weight 0.0031 kg

**Environmental Data** 

Operating temperature  $$-55\ ^{\circ}\text{C}$$  to 150  $^{\circ}\text{C}$$  2011/65/EU (RoHS) compliant

#### **Material Data**

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Bronze	Gold Plating (Nickel underplated)
Body	Brass	Nickel Plating
Insulator	PFA / PTFE	
Fastening nut	Brass	Nickel Plating
Washer	Brass	Nickel Plating

#### **Related Documents**

Catalogue drawing DCA-00010451 Mounting hole DOU-00009113

#### **Ordering Information**

Single package 22\_QLA-01-0-2/112\_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.