Data Sheet



Coaxial Panel Connector 23_PC35-50-0-53/199_U

Description

Straight panel receptacle jack, flange mount

Interface standards IEC 60169-23



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & 50 \ \Omega \\ \text{Interface frequency max.} & 26.5 \ \text{GHz} \end{array}$

Mechanical Data

Number of matings 500
Weight 0.0035 kg

Environmental Data

Operating temperature -60 °C to 100 °C 2011/65/EU (RoHS) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	PS (Polystyrene)	

Related Documents

Outline drawing DOU-00011352
Catalogue drawing DCA-00011353

Ordering Information

Single package 23 PC35-50-0-53/199 UE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.