Data Sheet

HUBER+SUHNER

Coaxial Panel Connector 13_BMA-50-0-2/199_N

Description

Straight panel receptacle plug, flange mount

Interface standards IEC 60169-33_MIL-STD-348A/321



Technical Data

Electrical Data		
Impedance	50 Ω	
Interface frequency max.	18 GHz	
Mechanical Data		
Number of matings	1000	
Weight	0.0025 kg	
Environmental Data		
Operating temperature	-65 °C to 125 °C	
2011/65/EU (RoHS - including	compliant	
2015/863 and 2017/2102)		
Material Data		
Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	PFA / PTFE	
Gasket	NR (Natural Rubber)	
Related Documents		
Catalogue drawing	DCA-00011086	
Ordering Information		
Single package	13_BMA-50-0-2/199_NE	

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.