

## Coaxial Cable Connector 11\_BNC-75-2-15/133\_N

### Description

Straight cable plug

Interface standards

Interface compatible with IEC 61169-8



### Technical Data

#### Electrical Data

Impedance 75  $\Omega$   
Interface frequency max. 1 GHz

#### Mechanical Data

Centre contact crimped  
Outer 2contact crimped  
Weight 0.0095 kg

#### Environmental Data

Operating temperature -65 °C to 165 °C  
2011/65/EU (RoHS) compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Bronze / Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
Crimp ferrule	Copper	

### Related Documents

Outline drawing DOU-00071335  
Catalogue drawing DOU-00006199  
Assembly instruction DOC-0000179123

### Ordering Information

Bulk 100 pcs package 11\_BNC-75-2-15/133\_NH  
Single package 11\_BNC-75-2-15/133\_NE

### Additional Information

Suitable cables RG\_179\_B/U, RG\_187\_A/U