Data Sheet

Coaxial Panel Connector 22_TNC-50-0-1/133_N

Description

Straight bulkhead receptacle jack

Interface standards IEC 60169-17_MIL-STD-348A/313_CECC 22200



Technical Data

Electrical Data	
Impedance	50 Ω
Interface frequency max.	11 GHz
Mechanical Data	
Number of matings	500
Weight	0.0118 kg
Environmental Data	
Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00048073
Catalogue drawing	DCA-00011037
Mounting hole	DOU-00010411

Ordering Information

Single package

22_TNC-50-0-1/133_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

