

## Coaxial Cable Connector 11\_BNC-50-7-1/133\_N

### Description

Straight cable plug

Interface standards

IEC 60169-8\_MIL-STD-348A/301\_CECC 22120



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 4 GHz

#### Mechanical Data

Centre contact soldered  
Outer 2contact clamped  
Weight 0.0367 kg

#### Environmental Data

Operating temperature -65 °C to 165 °C  
2011/65/EU (RoHS) compliant

#### Material Data

| Piece Parts    | Material              | Surface Plating                   |
|----------------|-----------------------|-----------------------------------|
| Centre contact | Brass                 | Gold Plating (Nickel underplated) |
| Outer contact  | Brass                 | SUCOPLATE (R) Plating             |
| Body           | Brass                 | SUCOPLATE (R) Plating             |
| Insulator      | PFA / PTFE            |                                   |
| Coupling nut   | Brass                 | SUCOPLATE (R) Plating             |
| Gasket         | VMQ (Silicone rubber) |                                   |

### Related Documents

Outline drawing DOU-00008406  
Catalogue drawing DOU-00006636  
Assembly instruction DOC-0000179854

### Ordering Information

Single package 11\_BNC-50-7-1/133\_NE

### Additional Information

Suitable cables RG\_213\_U, GX\_07272, G\_07262