Data Sheet

Coaxial PCB Connector 82_MMCX-50-0-18/111_O

Description

Straight PCB jack

Interface Standards SUHNER-MMCX



Gold Plating (without Nickel underplating)

Technical Data

Electrical Data		
Impedance	50 Ω	
Interface frequency max.	6 GHz	
Mechanical Data		
Board mounting type	surface mount	
Weight	0.0006 kg	
Environmental Data		
Operating temperature	-55 °C to 155 °C	
2011/65/EU (RoHS - including	compliant	
2015/863 and 2017/2102)		
Material Data		
Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (without Nickel underplating)

Related Documents

Outline drawing	DOU-00012647
Catalogue drawing	DCA-00085712
Mounting hole	DOU-00012649

Ordering Information

Tape and Reel package

82_MMCX-50-0-18/111_OM

Brass

PFA / PTFE

Remarks

Body

Insulator

PCB connector without stand-offs

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

HUBER+SUHNER