

## Within Series Adaptor 31\_PC185-50-0-1/199\_NE

### Description

Adaptor jack/jack  
PC 1.85 jack (female) / PC 1.85 jack (female)

For Test & Measurement applications  
Precision adaptor

Interface standard  
Series PC 1.85 - IEC 60169-32



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$		
Interface frequency max.	67 GHz		
Frequency range	DC to 15 GHz	15 to 25 GHz	25 to 67 GHz
Return loss	$\geq 30$ dB	$\geq 25$ dB	$\geq 20$ dB

#### Mechanical Data

Number of matings	500
Weight	0.011 kg

#### Environmental Data

Operating temperature	-55 °C to 155 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

#### Material Data

Interface - PC 1.85 jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO / Gold Plating
Outer contact	Stainless Steel	Passivated (Plating)
Body	Stainless Steel	Passivated (Plating)
Insulator	LCP (Liquid crystal polymer)	

Interface - PC 1.85 jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO / Gold Plating
Outer contact	Stainless Steel	Passivated (Plating)
Body	Stainless Steel	Passivated (Plating)
Insulator	LCP (Liquid crystal polymer)	

### Related Documents

Outline drawing	DOU-00282065
-----------------	--------------

### Ordering Information

Single package	31_PC185-50-0-1/199_NE
----------------	------------------------