Data Sheet

HUBER+SUHNER

Coaxial PCB Connector 85_BNC-75-0-1/133_N

Description

Right angle PCB jack

Interface Standards Interface compatible with IEC 61169-8



Technical Data

Electrical Data Impedance Interface frequency max.	75 Ω 1 GHz
Mechanical Data Board mounting type Weight	through holes 0.0152 kg
Environmental Data Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102)	-65 °C to 165 °C compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium / Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing	DOU-00012866
Catalogue drawing	DCA-00012868
Mounting hole	DOU-00012084

Ordering Information

Single package

85_BNC-75-0-1/133_NE

Remarks

PCB connector with stand-offs

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.