# **Data Sheet**

## Coaxial PCB Connector 85\_MCX-50-0-16/111\_N

### Description

Right angle PCB jack

Interface Standards IEC 60169-36\_CECC 22220





#### **Technical Data**

Electrical Data		
Impedance	50 Ω	
Interface frequency max.	6 GHz	
Mechanical Data		
Board mounting type	through holes	
Weight	0.0017 kg	
Environmental Data		
Operating temperature	-55 °C to 155 °C	
2011/65/EU (RoHS)	compliant	
Material Data		
Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PFA / PTFE	
Related Documents		
Outline drawing	DOU-00012853	
Catalogue drawing	DCA-00012855	
Ordering Information		
Tape and Reel package	85_MCX-50-0-16/111_NM	
Bulk 100 pcs package	85_MCX-50-0-16/111_NH	
Single package	85_MCX-50-0-16/111_NE	
Demerike		

#### Remarks

PCB connector with stand-offs

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.