

## Coaxial Cable Connector 24\_QLA-01-2-1/112\_N

### Description

Straight bulkhead cable feed through

Interface standards  
NIM-CAMAC-Standard CD/N549



### Technical Data

#### Electrical Data

Impedance	50 Ω
Interface frequency max.	1.4 GHz

#### Mechanical Data

Centre contact	soldered
Outer contact	crimped
Weight	0.0056 kg

#### Environmental Data

Operating temperature	-55 °C to 150 °C
2011/65/EU (RoHS)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Bronze	Gold Plating (Nickel underplated)
Body	Brass	Nickel Plating
Insulator	PFA / PTFE	
Fastening nut	Brass	
Washer	Brass	
Crimp ferrule	Copper	

### Related Documents

Catalogue drawing	DCA-00009112
Assembly instruction	DOC-0000179088
Mounting hole	DOU-00009113

### Ordering Information

Single package	24_QLA-01-2-1/112_NE
----------------	----------------------

### Additional Information

Suitable cables	RG_316_/U, RG_188_A/U, RG_174_/U
-----------------	----------------------------------