Data Sheet



Coaxial Panel Connector 22_BNO-0-0-2/133_N

Description

Straight bulkhead receptacle jack

Interface standards IEC 60169-22



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & \text{not defined } \Omega \\ \text{Interface frequency max.} & \text{0.2 GHz} \end{array}$

Mechanical Data

 Chassis torque
 2 Nm

 Number of matings
 500

 Weight
 0.0063 kg

Environmental Data

Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102)

-50 °C to 125 °C compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium / Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	ETFE (Ethylene tetrafluoroethylene)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating

Related Documents

Outline drawing DOU-00011411
Catalogue drawing DCA-00011413
Mounting hole DOU-00008762

Ordering Information

Single package 22_BNO-0-0-2/133_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.