Data Sheet


Coaxial PCB Connector 85_QLA-01-0-2/112_N



Description

Right angle PCB jack

Interface Standards
NIM-CAMAC-Standard CD/N549



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & 50 \ \Omega \\ \text{Interface frequency max.} & 1.4 \ \text{GHz} \end{array}$

Mechanical Data

Board mounting type through holes Weight 0.0048 kg

Environmental Data

Operating temperature $$-55\ ^{\circ}\text{C}$$ to 150 $^{\circ}\text{C}$$ 2011/65/EU (RoHS) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Bronze	Gold Plating (Nickel underplated)
Body	Brass	Nickel Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing DOU-00012841
Catalogue drawing DCA-00012843
Mounting hole DOU-00012844

Ordering Information

Single package 85_QLA-01-0-2/112_NE

Remarks

PCB connector without stand-offs

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.