Data Sheet

HUBER+SUHNER Excellence in Connectivity Solutions

Coaxial Cable Connector 11_SMA-50-3-16/-11_N

Description

Straight cable plug

Interface standards SUHNER-SMA-26.5GHz



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & 50 \ \Omega \\ \text{Interface frequency max.} & 26.5 \ \text{GHz} \end{array}$

Mechanical Data

Outer contact soldered
Weight 0.0019 kg

Environmental Data

Operating temperature -65 °C to 165 °C 2011/65/EU (RoHS) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact		
Outer contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Coupling nut	Bronze	Gold Plating (Nickel underplated)
Gasket	VMQ (Silicone rubber)	

Related Documents

Outline drawing DOU-00007822
Catalogue drawing DOU-00006518
Assembly instruction DOC-0000179294

Ordering Information

Bulk 100 pcs package 11_SMA-50-3-16/-11_NH

Additional Information

Suitable cables EZ_141_TP_M17

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.