Data Sheet

HUBER+SUHNER Excellence in Connectivity Solutions

Coaxial PCB Connector 92_SMA-50-0-10/111_N

Description

Straight PCB jack

Interface Standards
IEC 60169-15_MIL-STD-348A/310_CECC 22110



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & 50~\Omega \\ \text{Interface frequency max.} & 18~\text{GHz} \end{array}$

Mechanical Data

Board mounting type edge mount Weight 0.0044 kg

Environmental Data

Operating temperature $$-65\ ^{\circ}\text{C}$$ to 165 $^{\circ}\text{C}$$ 2011/65/EU (RoHS) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PTFE (Polytetrafluoroethylene)	

Related Documents

Outline drawing DOU-00088078
Catalogue drawing DCA-00181402

Ordering Information

Single package 92_SMA-50-0-10/111_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.