

## Between Series Adaptor 33\_MBX-SMA-50-1/111\_N

### Description

Adaptor plug/jack  
MBX plug (male) / SMA jack (female)

Interface standards  
Series MBX - HUBER+SUHNER MBX  
Series SMA - IEC 60169-15\_MIL-STD-348A/310\_CECC 22110



### Technical Data

#### Electrical Data

Impedance	50 Ω
Interface frequency max.	6 GHz
Frequency range	DC to 6 GHz
Return loss	≥ 28 dB

#### Mechanical Data

Number of matings	500
Weight	0.002215 kg

#### Environmental Data

Operating temperature	-55 °C to 155 °C
2011/65/EU (RoHS)	compliant

#### Material Data

Interface - MBX plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Bronze	SUCOPRO Plating
Body	Bronze	SUCOPRO Plating
Insulator	PFA / PTFE	

Interface - SMA jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Bronze	SUCOPRO Plating
Body	Bronze	SUCOPRO Plating
Insulator	PFA / PTFE	

### Related Documents

Outline drawing	DOU-00146084
-----------------	--------------

### Ordering Information

Single package	33_MBX-SMA-50-1/111_NE
----------------	------------------------