## **Data Sheet**

## **Coaxial PCB Connector** 82\_MMCX-S50-0-55/119\_O

## Description

Straight PCB jack

Interface Standards SUHNER-MMCX

## **Technical Data**

**Electrical Data** 

Impedance Interface frequency max.	50 Ω 6 GHz	
Mechanical Data Board mounting type	surface mount	
Weight	0.0002 kg	
Environmental Data		
Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102)	-40 °C to 90 °C compliant	
Material Data		
Piece Parts	Material	Surface Plating
Piece Parts Centre contact	Material Bronze	Surface Plating Gold Plating
		-
Centre contact	Bronze	Gold Plating
Centre contact Outer contact	Bronze Brass	Gold Plating
Centre contact Outer contact Body	Bronze Brass	Gold Plating
Centre contact Outer contact Body Related Documents Outline drawing	Bronze Brass LCP (Liquid crystal polymer) DOU-00080629	Gold Plating

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.



