# **Data Sheet**



# Coaxial PCB Connector 85\_MMCX-S50-0-55/119\_O

# **Description**

Straight PCB jack

Interface Standards
SUHNER-MMCX



# **Technical Data**

**Electrical Data** 

 $\begin{array}{ll} \text{Impedance} & 50 \, \Omega \\ \text{Interface frequency max.} & 6 \, \text{GHz} \end{array}$ 

**Mechanical Data** 

Board mounting type surface mount Weight 0.0002 kg

**Environmental Data** 

Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102) -40 °C to 90 °C compliant

#### **Material Data**

Piece Parts	Material	Surface Plating
Centre contact	Bronze	Gold Plating
Outer contact	Brass	Gold Plating
Body	LCP (Liquid crystal polymer)	

### **Related Documents**

Outline drawing DOU-00080841 Mounting hole DOU-00012840

# **Ordering Information**

Tape and Reel package 85\_MMCX-S50-0-55/119\_OM

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.