

Coaxial Cable Connector 21_MCX-50-2-13/111_N

Description

Straight cable jack

Interface standards

IEC 60169-36_CECC 22220



Technical Data

Electrical Data

| | |
|--------------------------|-------------|
| Impedance | 50 Ω |
| Interface frequency max. | 6 GHz |

Mechanical Data

| | |
|----------------|-----------|
| Centre contact | crimped |
| Outer contact | crimped |
| Weight | 0.0014 kg |

Environmental Data

| | |
|-----------------------|------------------|
| Operating temperature | -55 °C to 155 °C |
| 2011/65/EU (RoHS) | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|------------------------|-----------------------------------|
| Centre contact | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Outer contact | Brass | Gold Plating (Nickel underplated) |
| Body | Brass | Gold Plating (Nickel underplated) |
| Insulator | PFA / PTFE | |
| Crimp ferrule | Copper | |

Related Documents

| | |
|----------------------|----------------|
| Outline drawing | DOU-00007141 |
| Catalogue drawing | DOU-00006340 |
| Assembly instruction | DOC-0000179868 |

Ordering Information

| | |
|----------------------|-----------------------|
| Bulk 100 pcs package | 21_MCX-50-2-13/111_NH |
| Single package | 21_MCX-50-2-13/111_NE |

Additional Information

| | |
|-----------------|--|
| Suitable cables | RG_316_U, ENVIROFLEX_316, RG_188_A/U, RG_174_U |
|-----------------|--|